

# NVR3216V-P

## 16 Channel 2HDD PoE Vertical Network Video Recorder



### Features

- > Up to 16 channel with 1080p realtime live view
- > H.264/MJPEG dual codec decoding
- > Max 120fps@1080p, 240fps@720p,480fps@D1 preview & recording
- > All channel simultaneous realtime playback, GRID interface & smart search
- > Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotech and etc.
- > ONVIF Version 2.0 conformance
- > 3D intelligent positioning with Dahua PTZ camera
- > Support 2 SATA HDDs up to 8TB, 1 eSATA up to 16TB, 3 USB2.0
- > Support IPC UPnP, 4 PoE ports
- > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS


<b>Model</b>	<b>NVR3216V-P</b>
<b>System</b>	
Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
<b>Video &amp; Audio</b>	
IP Camera Input	16 channel

# NVR3216V-P

Two-way Talk	1 channel Input, 1 channel Output, RCA
<b>Display</b>	
Interface	1 HDMI, 1 VGA
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
Display Split	1/4   1/4/8/9   1/4/8/9/16
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
<b>Recording</b>	
Compression	H.264 / MPEG4
Resolution	1080P(1920×1080) / 720P(1280×720) / D1 (704×576/704×480)
Record Rate	400/480fps@D1, 200/240fps@720P, 100/120fps@1080P
Bit Rate	48 ~ 8192kbps
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
<b>Video Detection &amp; Alarm</b>	
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank
Alarm Input	3 channel
Relay Output	1 channel
<b>Playback &amp; Backup</b>	
Sync Playback	1/4/9/16
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / eSATA Device / Network
<b>Network</b>	
Ethernet	RJ-45 port (10/100M/1000M)
PoE	4 ports (IEEE802.3af)
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support Dahua IP camera, DVR, NVS etc)
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
<b>Storage</b>	
Internal HDD	2 SATA ports, up to 8TB
External HDD	1 eSATA port (Max 4 SATA HDDs), up to 16TB
<b>Auxiliary Interface</b>	
USB Interface	3ports (1 Rear), USB2.0
RS232	1 port, For PC communication & Keyboard
RS485	1 port, For PTZ control
<b>General</b>	
Power Supply	NVR: DC12V

# NVR3216V-P

	PoE Switch: DC48V
Power Consumption	NVR: 20W(without HDD)
	PoE Port: Max.15 (each)
Working Environment	-10 ~ +55°C / 10~90%RH / 86~106kpa
Dimension (W×D×H)	100mm×220mm×146mm
Weight	1.6KG(without HDD)



Secrets Of Systems .  
 King Abdullah Road, Saudi Arabia.  
 Tel: +966-1-2493221  
 Fax: +966-1-2493220  
 Email: sales@ssesa.com  
 www.ssesa.com