

Car Camera/IP/Network Products

Car Camera

SS-C100

- 1/3" Sony Color CCD 540/420TVL
- Mini Illumination 0.05Lux
- 2.5/2.8/3.6/6mm Fixed Lens optional
- 12EA LED with 5-10m IR Distance
- DC12V250mA
- IP67 Ingress Protection
- Suitable for outdoor installation of bus/car/truck

SS-C101

- 1/3" Sony Color CCD 540/420TVL
- Mini Illumination 0.05Lux
- 2.5/2.8/3.6/6mm Fixed Lens optional
- 12EA LED with 5-10m IR Distance
- DC12V250mA
- Suitable for indoor installation of bus/car/truck

SS-C102

- 1/3" Sony Color CCD 540/420TVL,0.05Lux
- 2.5/2.8/3.6/6mm Fixed Lens optional
- IP67 Ingress Protection
- DC12V 100mA
- Camera Size 73*73*57.3mm179g/pcs
- Suitable for outdoor installation bus/car/truck/taxi

SS-C102-IR

- 1/3" Sony Color CCD 540/420TVL,0.05Lux
- 2.5/2.8/3.6/6mm Fixed Lens optional
- 10EA LED with 5-10m IR Distance
- IP67 Ingress Protection
- DC12V 250mA
- Camera Size 73*73*57.3mm 179g/pcs
- Suitable for outdoor installation bus/car/truck/taxi

SS-C103

- 1/3" Sony Color CCD 540TVL,0.05Lux
- 2.5/2.8/3.6/6mm Fixed Lens optional
- 12EA 5-10m IR Distance
- Voltage with DC12V 250mA
- Camera size 54*54*50mm106g/pcs
- IP66 Ingress Protection
- Black Color Casing
- Suitable for indoor installation for bus/car/truck/taxi

IP/Network Products

SS-IP11

- Resolution 1920*1080, real-time image, (1280*720,real-time option)
- 1/3 Progressive Scan (WDR) CMOS ,motion images without jagged
- 2.8-12mm DC ICR Lens, Support Color/BW mode ,IR-CUT
- 42 IR LED lights, IR working distance: 30m
- Support H.264/MJPEG video encoding, dual-stream
- Embedded Web Server, support IE browser, user management, ONVIF protocol support

IP Standard Box Cameras

- Model NO.: SS-IP11/12/13/14/460/457
- Sony CCD or OV CMOS optional,1.3Mpixel/2.0Mpixel/D1 Resolution optional
- Embedded System+Hi3512/ARM9,32 bit RISC,16MB Flash, 128MB Memory
- Mobile Monitoring OS:Windows Mobiles 6.0 or above / Symbian S60 3rd and 5th / Iphone
- 1CH CVBS Video loopback output / 1CH Mic input and 1CH linear output
- Support H.264/MJPEG video encoding, dual-stream, high compression ratio
- Embedded Web Server, support IE browser, user management, ONVIF protocol support
- Support SD Card Slot3G ,Wifi and POE function optional

SS-IP12

- Resolution 1920*1080, real-time image,(1280*720,real-time option)
- 1/3 Progressive Scan (WDR) CMOS ,motion images without jagged
- 2.8-12mm DC ICR Lens, Support Color/BW mode,IR-CUT
- 21 IR LED lights, IR working distance: 15m
- Support H.264/MJPEG video encoding, dual-stream
- Embedded Web Server, support IE browser, user management, ONVIF protocol support

SS-IP14

- Resolution 1920*1080, real-time image,(1280*720,real-time option)
- 1/3 Progressive Scan CMOS (1/3 Progressive Scan CCD option)
- Captures motion images without jagged
- 5-15mm DC ICR Lens, Support Color/BW mode converting ,IR-CUT
- 4 high power IR LED lights(third-generation), IR working distance: 50m
- Support H.264/MJPEG video encoding, dual-stream
- Embedded Web Server, support IE browser, user rights management ONVIF protocol support

SS-IP13

- Resolution 1920*1080, real-time image,(1280*720,real-time option)
- 1/3 Progressive Scan (WDR) CMOS ,motion images without jagged
- 2.8-12mm DC ICR Lens, Support Color/BW mode ,IR-CUT
- 15 IR LED lights, IR working distance: 10m
- Support H.264/MJPEG video encoding, dual-stream
- Embedded Web Server, support IE browser, user management, ONVIF protocol support

SS-IP460/IP457

- Embedded System+Hi3512 /ARM9,32 bit RISC,16MB Flash, 128MB Memory
- H.264 Main Profile@Level 3.0/MJPEG,Support SD Card Slot
- Mobile Monitoring OS:Windows Mobiles 6.0 or above / Symbian S60 3rd and 5th / Iphone
- 1CH CVBS Video loopback output / 1CH Mic input and 1CH linear output
- Support H.264/MJPEG video encoding, dual-stream, high compression ratio
- Embedded Web Server, support IE browser, user management, ONVIF protocol support

DVR

SS-D1104A/D1108A



- 4/8 Channel Standalone DVR
- Linux Operation system,H.264 Compression/AVI
- Record Frame Rate Support D1/HD1/CIF
- Remote Client,IE Brower,Mobile,CMS,Alarm
- RS485,VGA,SATA 2.6*1(1*HDD 2TB)
- 2*USB2.0,USB Disk up to 32G,Removable DVD-RW

SS-D2204A-S/D2208A-S/D3216A-S



- 4/8/16 Channel Standalone DVR
- Linux Operation system,H.264 Compression/AVI
- Record Frame Rate Support D1/HD1/CIF
- Remote Client,IE Brower,Mobile,CMS,Firefox, Google Chrome,Mac Safari
- Talk Back,Loop Out,RS485,VGA,SATA 2.6*1(2*HDD 2TB)
- 2*USB2.0,USB Disk up to 32G,DVD±RW,SD Card up to 32GB
- 3G Device Win Mobile5.0/6.0,Symbian,PDA,Blackberry, Iphone(recommended)

SS-D2104A-A/D2108A-A/D2116A



- 4/8/16 Channel Standalone DVR
- Linux Operation system,H.264 Compression/AVI
- Record Frame Rate Support D1/HD1/CIF
- Remote Client,IE Brower,Mobile,CMS,Firefox, Google Chrome,Mac Safari
- Talk Back,RS485,VGA,SATA 2.6*1(2*HDD 2TB)
- 2*USB2.0,USB Disk up to 32G,Removable DVD-RW

SS-D2104B/D2108B/D2116B



- 4/8/16 Channel Standalone DVR
- Linux Operation system,H.264 Compression/AVI
- Record Frame Rate Support D1/HD1/CIF
- Remote Client,IE Brower,Mobile,CMS,Firefox, Google Chrome,Mac Safari
- Talk Back,RS485,VGA,SATA 2.6*1(2*HDD 2TB)
- 2*USB2.0,USB Disk up to 32G,Removable DVD-RW

SS-D4408A/D4416A



- 8/16 Channel Standalone DVR Linux Operation system, H.264 Compression/AVI
- Record Frame Rate Support D1/HD1/CIF
- Remote Client,IE Brower,Mobile,CMS,Firefox, Google Chrome,Mac Safari
- Talk Back,Loop Out,RS485,VGA,SATA 2.6*1(4*HDD 2TB)
- 2*USB2.0,USB Disk up to 32G,DVD±RW,SD Card up to 32GB
- 3G Device Win Mobile5.0/6.0,Symbian,PDA,Blackberry, Iphone(recommended)
- HD VGA Output; HDMI 1080P Output optional

SS-D5508A/D5516A/D5532A



- 8/16/32 Channel D1 Standalone DVR Linux Operation system, H.264 Compression/AVI
- Record Frame Rate Support D1/HD1/CIF
- 2 CH BNC;HD VGA Output;HDMI 1080P Output optional
- Remote Client,IE Brower,Mobile,CMS,Firefox, Google Chrome,Mac Safari
- Talk Back,Loop Out,RS485,VGA,SATA 2.6*1(8*HDD 2TB)
- 2*USB2.0,USB Disk up to 32G,DVD±RW,SD Card up to 32GB
- 3G Device Win Mobile5.0/6.0,Symbian,PDA,Blackberry, Iphone(recommended)



SECRETS OF SYSTEMS

New Products

SS-W1103SNH-3NVP

- 1/3" Sony Color CCD 600TVL
- 4-9mm DaiWon Manual Lens, 0Lux
- 48EA LED, 40-50M IR Distance
- OSD option, Anti-thunder, IP67



Another Eye Guarding the world

SS-W115SNH-2

- 1/3" Sony Color CCD 540TVL
- 4-9mm Manual VF Lens
- Infrared LED: 42EA, IR Distance: 40m
- Waterproof Standard: IP66



SS-W118SNH-3NVP

- 1/3" Sony Color CCD, 600TVL
- 3.6 MM Daiwon Fixed lens
- Infrared LED: 24EA, IR Distance: 20-30Meters
- Waterproof IP67, Anti-Thunder Design



SS-67SN

- 1/3" Sony Super-Had CCD 420TVL
- 3.6 MM Fixed lens
- Infrared LED: 36EA IR Distance: 30Meters
- Waterproof Ip57



SS-B602SNH-3NVP

- 1/3" Sony Super-Had CCD 600TVL
- OSD, 2D-DNR, D-WDR



SS-D206SNH-3NVP-OSD

- 1/3 SONY Color CCD 600TVL
- OSD, 2DDNR, D-WDR, IR-SMART
- 4-9mm Manual varifocal lens
- Infrared LED: 17EA, IR Distance: 20Meters



SS-D201SN

- 1/3" Sony Super-Had CCD 420TVL
- 3.6 MM Fixed lens
- Infrared LED: 22EA, IR Distance: 20Meters
- With Audio



CCTV Cameras

PIXIM Seawolf



SS-D205PIXIM-1



SS-D210PIXIM-1



SS-406PIXIM-1



SS-VD225PIXIM-1



SS-804PIXIM-1



SS-1125PIXIM-1



SS-1126PIXIM-1



SS-1127PIXIM-1



SS-W1103PIXIM-1



SS-W1104PIXIM-1



SS-55PIXIM-1



SS-B602PIXIM-1



SS-500PIXIM-1



SS-D231PIXIM-1



SS-M137PIXIM-1

700TVL High Resolution Camera



SS-223SNH-4



SS-147SNH-4



SS-B603SNH-4



SS-W1104SNH-4



SS-W116SNH-4



SS-W119SNH-4



SS-1160SNH-4



SS-1161SNH-4



SS-1135SNH-4



SS-1141SNH-4



SS-W922SNH-4



SS-123SNH-4



SS-VD602SNH-4




SS-406SNH-4



SS-VD406SNH-4



SS-406(V2)SNH-4




SS-D220SNH-4



SS-VD225SNH-4



SS-D210SNH-4



SS-504SNH-4

The Third Generation Infrared Array Series



SS-W134



SS-W133



SS-VD232



SS-W201



SS-W1105



SS-W1104

SS-PTZ470IR

- Pan speed 0.1°--240°/s, Tilt speed 0.1°--120°/s
- English OSD menu, menu password protection
- 128 preset positions, 2 scan modes, 4 patrol, 8 pattern tracks
- Privacy zone function
- RS485, PelcoD, P protocol auto detect
- High quality motor provide stable and low noise performance
- Privacy zone protection
- Leisure action setup
- Pan/tilt position and zoom times displayable
- Clock and temperature info displayable
- Aluminum alloy vandal proof housing
- Fan and heater inside, IP66 Ingress Protection
- 4000V lightning proof capability
- DC 13.5V power input



The Third Generation Infrared Array Speed Dome shines, even in the Dark with 100Meters Visible Distance.

EASY & LOCK

Mini 10X High Speed Dome Camera



SS-PTZ471

- Pan 360 degree continuous rotation, Tilt 180 degree Auto flip
- Pan speed 0.1°--240°/s, Tilt speed 0.1°--240°/s
- English OSD menu, menu password protection
- 128 preset positions, 2 scan modes, 4 patrol, 8 pattern tracks
- RS485, PelcoD, P protocol auto detect
- Leisure action setup
- Pan/tilt position and zoom times displayable
- Aluminum alloy vandal proof housing
- Fan and heater inside
- 4000V lightning proof capability
- DC12V power input



http://www.ssesa.com
Tel: +966 1 4938221
Fax: +966 1 493220
Email: Sales@ssesa.com
P.O. Box: 104305, Riyadh, 11626
Kingdom of Saudi Arabia