

SS-PTZ471INK-Alarm



Feature

- Indoor Integrative Speed Dome Camera
 - Samsung 10X Zoom Module optional
 - Address 0~255, Pan 360° continuous pan rotation Tilt 180°, 128 Presets
 - 4 Article PTZ Tours (Pattern)
 - 4 Article Vector scan groups and 128 Presets
 - Coaxial line for Wiring
 - RS-485 communication, Integrative Power Off real time memory
 - 12VDC/2A Power supply, 10W Power Consumption
 - Embed in surge and lightning protector
 - Alarm Optional
-

Model NO.	SS-PTZ471INK-Alarm
Operation	
OSD menu	English
Preset position	128 Preset Positions
Scan	Auto scan and left-right limited scan, speed adjustable
Patrol	4tracks, 16 preset per track, speed and dwell time changeable
Pattern	4 tracks
Alarm	N/A
Private masking	4 Privacy Mask
Address range	0--255
Communication	RS485 (+/-)
Baud rate	2400/4800/9600/19200, setup by dip switcher
Protocol	Pelco-P/D auto detected, or others customized
Leisure action	Home place/Scan/Patrol/Pattern
Device title	Display on/off
P/T position	Display on/off
Temperature info	Display on/off
Zoom times	Display on/off
Mechanical	
Pan range	0°~ 360° continuously
Pan speed	0.1~ 240°/s
Tilt range	0°~ 180° auto flip on/off performance
Tile speed	0.1~ 240°/s
Precision	0.1°
Others	
Housing	Aluminum alloy, vandal proof housing
Lighting proof	N/A
Water proof	IP66
Heater&Fan	N/A
Work temp	0°C~ 50°C (with fan and heater, work temp. is -30°C~ 70°C)
Work humidity	Max 95%
Power	DC12V
Installation	indoor installation
Zoom lens option	
SDM-100	Samsung 10x zoom D/N, 1/4" Super HAD CCD 500TVL, f=3.8 to 38mm(F 1.8 to 3.2), Color:0.7Lux, B/W:0.02Lux, SSNR