

## SS-PTZ470IR



### Feature

- Indoor/Outdoor Integrative Speed Dome Camera
  - Address 0~255, Pan 360° continuous pan rotation, Tilt 90° Auto flip 18, 128 Presets
  - 2 Article PTZ Tours (Pattern)
  - 4 Article Vector scan groups
  - Coaxial line for Wiring
  - 100m IR Distance
  - RS-485 communication, Integrative Power Off real time memory
  - DC12V/5A Power supply, 36W Power Consumption
  - Embed in surge and lightning protector
  - Alarm Optional
-

Model NO.	SS-PTZ470IR
<b>Operation</b>	
OSD menu	English, password protection
Preset position	128
IR LED	Φ8mm /24 10 wing high-power infrared lamp
IR-LED distance	100m
IR-LED Mode	close range/middle-distance/ long-distance
Scan	Auto scan and left-right limited scan, speed adjustable
Patrol	4 tracks, 16 preset per track, speed and dwell time changeable
Pattern	2 tracks, max 15 minutes for each
Alarm	2 input, 2 output option
Private masking	Supported function based on zoom module
Address range	0~255
Communication	RS485
Baud rate	2400/4800/9600/19200, setup by dip switcher
Protocol	Pelco-P/D auto detected, or others customized
Leisure action	Home place/Scan/Patrol/Pattern
Device title	Display on/off
P/T position	Display on/off
Zoom times	Display on/off
Clock Time	Display on/off
Temperature info	Display on/off
<b>Mechanical</b>	
Pan range	0°~ 360° continuously
Pan speed	0.1~ 240°/s
Tilt range	0°~ 90° auto flip on/off performance
Tilt speed	0.1~ 120°/s
Precision	0.1°
<b>Others</b>	
Housing	Aluminum alloy, vandal proof housing
Lighting proof	With 4000V video, data and power lighting proof
Water proof	IP66
Work temp	-40°C~ 70°C
Work humidity	Max 95%
Power	DC12V
Installation	Outdoor and indoor installation
Package size	42x31x31cm
Package weight	8kg
<b>Zoom lens</b>	
CNB-21Z27F	CNB 27x zoom, D/N, 1/4" High Sensitivity CCD II(Color:580TVL B/W:640TVL), f=3.6-97.2mm(F=1.6),Color:1Lux, B/W:0.5Lux, DSS:0.001Lux,IR -CUT,3DDNR