

SS-ND103AN1-WISM



MODELS	SS-ND103AN1-WISM
Image Sensor	
Image Sensor	1/5" CMOS Sensor
Horizontal resolution	420TVL
Min. Illumination	Color 0.1Lux@(F1.2 AGC on),0Lux with IR; B/W 0.01Lux@(F1.2 AGC on),0Lux with IR
Lens	
Lens Mount Type	M12
Lens	4mm@ F: 2.0
Video	
Image Compression	H.264
Image Frame rate	50Hz:25fps (640*480) 60Hz:30fps (640*480)
Flip Mirror Images	Vertical / Horizontal
Light Frequency	50Hz, 60Hz
Video Parameters	Saturation, Brightness, Contrast adjustable
Night Visibility	11 IR LEDs, Night visibility up to 10 meters
Audio	
Audio Compression	G.711A
Input	1 channel micro interface
Output	1 channel 3.5mm jack interface
Alarm	
Input	1channel

Output	1channel
PT function	
Pan range	270°
Tilt range	90°
Storage	
TF card slot	32GB (max)
PC Requirements	
CPU	2.0GHz or above (suggested 3.0GHz)
Memory Size	256MB or above (suggested 1.0GB)
Display Card	64MB or above
Supported OS	Microsoft Windows 2000/XP, Vista, Windows7, Mac OS, Linux
Browser	IE6/IE7/IE8/IE9, Firefox, Safari, Goolge Chrome
Smart phone Support	
Support phone	Iphone, Blackberry, Android, Symbian, Windows Mobile
Power	
Power Supply	DC 5V/2A (EU, US, AU, UK plug)
Power Consumption	5 Watts (Max.)
Network	
Ethernet	One 10/100Mbps RJ-45
Supported Protocol	HTTP, FTP, RTSP, TCP/IP, UDP, SMTP, DHCP, PPPoE, DDNS, UPnP, NTP
Wireless	
Wireless Standard	IEEE 802.11b/g/n
Data Rate	802.11b: 11Mbps(Max.) 802.11g: 54Mbps(Max.)
Wireless Security	WEP & WPA & WPA2 Encryption
Physical	
Dimension(L x W x H)	91 x 103 x 135mm
Gross Weight	635g (Color Box Size: 217 x 170 x 136mm)
Net Weight	277g (accessories excluded)
Environment	
Operating Temp.	-10°C ~ 60° (14°F ~ 140°F)
Operating Humidity	0% ~ 90% non-condensing