

## SS-NP6061F-A-Q27



### Feature

- Support 256 presets, 32-bit software address
  - 32-bit ARM processor CPU, User management protection
  - 8 mission planning and 8 Editable vector path
  - 6 pattern (horizontal/vertical/zoom, and each can record up to 120 seconds)
  - Compatability with all Protocol: PELCO-D, PELCO-P, ULTRACK, VICON, DYNACOLOR
  - Compatible with Sony.
- Optional multi-language:(English, Chinese, German, French, Russian, Italian, Spanish) optional



Model No.	SS-NP6061F
<b>Operation</b>	
OSD menu	English,Chinese,Spanish,Russian Optional
Preset position	128 or 256 Preset Positions Optional
Scan	Auto scan and left-right limited scan, speed adjustable
Patrol	8 tracks, preset, speed and dwell time changeable
Pattern	6 Lines(Pan/Tilt/Zoom, every line can record up to 120 seconds)
Alarm	4 or 8 alarm inputs optional, 2 alarm outputs
Password protection	YES
Temperature display and Settings	YES(Temperature alarm set, Temperature Display)
Authority Management	YES
Private masking	8 zones
Address range	0~255 (Setup by dip switcher, firmware and network)
Communication	RS485 (+/-)
Baud rate	2400/4800/9600/19200, setup by dip switcher
Protocol	PELCO-D, PELCO-P , ULTRACK, VICON, DYNACOLOR
Device title	Display on/off
Zoom times	Display on/off
<b>Mechanical</b>	
Pan range	0°~ 360° continuously
Pan speed	0.1~ 360°/s
Tilt range	0°~ 180° auto flip on/off performance
Tile speed	0.1~ 180°/s
Precision	±0.10°
<b>Others</b>	
Housing	Aluminum alloy, vandal proof housing,Wall Mount,Ceiling Mount
Lighting proof	6000V
Water proof	IP67
Work temp	-40℃~+60℃
Work humidity	0%~90%
Power	24V AC 2A 60Hz/50Hz 35W
<b>Zoom lens option</b>	
Optional Zoom Brand	Sony  Sony 27x zoom,1/4" 48TVL f=3.9~105.3mm(F=1.6),Color 0.02Lux,B/W0.001Lux / 0Lux,IR-CUT,color to B/W

Secrets Of Systems .  
 King Abdullah Road, Saudi Arabia.  
 Tel: +966-1-2493221  
 Fax: +966-1-2493220  
 Email: sales@ssesa.com  
 www.ssesa.com